


CMT-632 FLUSH SMOOTH STEEL INSULATED DOOR

SERIES FEATURES


- 1 3/8" (34.9mm) Thick Polyurethane. Haas Door is compliant with HFC regulations on our polyurethane products.
- 0.106 Tested U-Factor
- 20-Gauge Galvanized Steel
- Meets ASHRAE 90.1 Air Infiltration Requirements
- Full Thermal Break
- Available with Wind Load and Impact Options
- 2 Color Options
- 10-Year Rust & Delamination Warranty
- 1-Year Hardware
- 1-Year Spring

Cross Section



**1 3/8" (34.9mm)
Thick Sections**

AVAILABLE COLORS



Colors are not exact due to the differences in monitor and printer calibrations. For accurate color samples, contact Haas Door for a metal color selector.

MODEL FEATURES

- 16 ga. Galvanized Steel End Stiles
- 20 ga. flush smooth outside and 26 ga. V-groove pattern wood grain embossement inside
- Tongue and groove section joint
- TL Window Optional

Exterior View



Interior View



600 SERIES LINKS

Click links for info.

[HOMEPAGE](#)

[BIM](#)

[BROCHURE](#)


[SPECS](#)

[GALLERY](#)

[SPECWIZARD](#)

[CAD](#)

[CATALOG](#)



U-Factor uses a solid door assembly. Adding lites will affect the tested U-Factor.

Rev. 2.7 – June 2023